

# PORTABLE INTERFACE (PI)



The L3 Portable Interface (PI) is a handheld portable interface device for data retrieval from FA2100 recorders. The user interface, a seven-key keypad and an eight-line display, allows stand-alone operation to perform the following functions: Flight Data Recorder (FDR), Cockpit Voice Recorder (CVR) and Cockpit Voice and Data Recorder (CVDR) monitor, copy and playback.



## **FEATURES**

- Provides digital data copy FDR, CVR and CVDR with time tag from the FA2100 recorder
- High-capacity PC card (PCMCIA) allows storage of data from multiple aircraft flights
- Simultaneous CVR reproduction of six analog channels
- Real-time audio monitoring
- Rapid FDR data retrieval on aircraft
- Menu-driven user interface with fault output display capability
- Powered by the FA2100 FDR, CVR and CVDR recorder

Use of U.S. DoD visual information does not imply or constitute DoD endorsement.

# PORTABLE INTERFACE (PI)



## SPECIFICATIONS

### PHYSICAL DIMENSIONS

Height	10.5 in. (267 mm)
Width	5.5 in. (140 mm)
Depth	2 in. (51 mm)
Weight	> 3 lbs. (0.91 kg)

### POWER

Power to operate the Portable Interface is obtained from the FA2100 recorder (CVR/FDR/CVDR)

### CONNECTOR

26-pin ATE interface to FA2100

### MONITOR OUTPUTS

Auxiliary output monitor for rotor speed/GMT/FSK, headphone jack, 600  $\Omega$  for monitoring any, or all audio channels

### DATA MONITORING

Rotor speed/FSK output

GMT/FSK output via 1/8-in. stereo jack

Monitored playback audio via 1/4-inch

600  $\Omega$  phone jack

Internal speaker and individual audio channels via 9-pin DIN connector

### DATA RETRIEVAL

Real-time audio (all channels)

Playback of audio (all channels)

Download of digital audio data to hard disk

Playback of audio from hard disk via Portable Interface

Real-time raw flight data

Full or partial download of digital flight data

### ENVIRONMENTAL

Temperature (operating)	0 °C to +50 °C
Storage	-20 °C to +60 °C
Vibration	None
Impact	None
Humidity and Liquid Submersion	None

### COMPANY CERTIFICATION

L3 Aviation Products Quality Management System is ISO 9001:2008 and AS9100:2009 Rev. C Certified

©2017 L3 Aviation Products • Printed in USA



Handheld Portable Interface device for data retrieval from FA2100 recorders



High-capacity PC card (PCMCIA) allows for storage of data from multiple aircraft flights

## L3 Aviation Products

100 Cattlemen Road

Sarasota, Florida 34232 U.S.A.

Tel: 941-371-0811 Fax: 941-377-5591

[www.L3aviationproducts.com](http://www.L3aviationproducts.com)



L3 Aviation Products is a leading provider of commercial and military avionics, as well as MRO services. We manufacture a diverse line of safety- and efficiency-enhancing products that sets the standard for next-generation cockpit requirements.